

FUSION SYSTEMS

CHEMILUMINESCENCE &
FLUORESCENCE IMAGING



Made in France



WESTERN BLOT & GEL DOCUMENTATION IMAGING

VILBER
Smart Imaging

The FUSION FX's protocol driven image acquisition is as quick as it is intuitive: adjust your exposure, save, print or quantify.



The FUSION FX delivers more significant quantitative data compared to other imagers.

For chemiluminescence, the time to get the image is dramatically reduced and precious antibody can be saved.

RELIABLE DATA FOR QUANTIFICATION PRECISE AND ACCURATE

The FUSION FX is ideal for quantification grade imaging. Chemiluminescent Western blot data poses distinct challenges in producing quantifiable, reproducible data. These problems stem from a low-dynamic range of detection and the difficulty in accurately determining the limit of detection. The FUSION FX eliminates all these issues thanks to its High Sensitivity Reading (HSR) camera technology which delivers reliable dynamic range, linearity and sensitivity for the lowest limit of detection. With the HSR, the FUSION FX reduces the various sources of noise to the lowest floor level and the signal can stand out from the surrounding background.

The FUSION FX provides consistent and reproducible data, independently of the chemiluminescence time course. The chemiluminescence intensity/time profile consists of an initial rise period up to a prolonged emission at a pseudo-plateau level and a decline. The FUSION FX Automatic imaging mode compensates the time course of the chemiluminescence reaction by adjusting the exposure time while maintaining the larger possible image dynamic.

CUSTOM MADE V.070 LENS UNRIVALLED SENSITIVITY

The FUSION FX custom made V.070 lens combines sensitivity and optical performance for very faint light

conditions. The optical system includes ultra-low dispersion components to enhance the sensitivity, and aspheric elements to deliver consistently sharp images. The V.070 lens has a focusing distance of only 20cm for the best sensitivity, clarity and image quality. The main function of a camera lens is to collect light. The lens aperture represents its capability to collect as much light as possible in a given period. Its sensitivity is usually expressed by a range of f-stops. The smaller the f-stop number, the larger the aperture. A lower f-number denotes a greater aperture opening, which allows more light to reach the CCD sensor. The aperture of the V.070 lens is f/0.70, providing faster imaging and better sensitivity compared to all other imagers.

DESIGN FOR SIMPLICITY ONE CLICK TO THE IMAGE

The FUSION FX has been designed for maximum ease of use. From its simple installation to its intuitive user interface, this system is plug and-play. The FUSION FX software is the easiest software to take an image. Place your blot on the tray, select your application, click on Start and automatically the system auto-exposes your blot image, your marker image and combines the two together.

The FUSION FX includes our unique Apps Studio approach to imaging. The Apps Studio is a library which contains 40 different protocols for your blot, gel and other bioluminescence samples. The protocol oriented Apps Studio ensures reproducibility and one click acquisition for the best ease of use.

For fluorescence, photobleaching and phototoxicity are reduced.

New Edge Generation



FUSION FX



SUPERIOR QUANTITATIVE RESULTS

Ultimate linearity for precise protein quantification over the full dynamic range.



HIGH SENSITIVITY READING (HSR) TECHNOLOGY

Ultra-low noise imaging thanks to a dual camera amplifier architecture.



CUSTOM MADE LENS

FUSION FX custom made lens for enhanced sensitivity and sharpness.



SUPER SENSITIVITY

Time to get the image is drastically reduced and precious antibody can be saved.

QUANTITATIVE WESTERN BLOTTING


Sensitivity is a key feature to detect a protein expressed at low levels. Broad linear dynamic range is necessary to compare weak and strong signals in the same image.

The FUSION FX has a limit of detection in the picogram level.


The system achieves the best signal to noise ratio for the lowest limits of detection. The FUSION

FX is extremely linear over its wide dynamics and can easily detect large intensity difference between bright and faint bands before reaching saturation. The broad linear dynamic range enables relative quantification of target proteins with confidence.

BROADEST LINEARITY



PICOGRAM LEVEL OF DETECTION & WIDE DYNAMIC RANGE





FUSION FX

*New Edge Generation
The Unrivalled Sensitivity*

Camera & Optics

FUSION FX6 with the eVo-6 camera – resolution oriented camera ideal for publication

eVo-6 camera:

- Unrivalled custom made lens f/0.70
- Scientific grade CCD camera
- Grade 0, zero defect
- Image resolution: 20 megapixels
- Native resolution: 2838x2224
- -55° C maximum cooling differential from ambient
-30°C absolute and regulated cooling via three stages Peltier thermoelectric cooler
- High Sensitivity reading (HSR) technology
- USB-3 connection

Ease Of Use

One-Click-to-the-Image™
Auto-exposure, Auto-focus
Auto-lighting

Hardware

Smart Darkroom technology:

- Motorised optical lens
- 6 positions filter wheel
- Software control of the lighting
- Automatic recognition of the sample position
- Automatic visible lighting adjustment

Steel and stainless steel darkroom for long lasting robustness. Wide access door with UV safety shut-off
Built-in slide-out tray for interchangeable Pad.
Built-in Spectra Capsules Adapter

Software

Free software for image acquisition with full GLP compliance. Molecular weight calculation, band quantification, colony counting, distance calculation, text annotation and image enhancement included.

CFR21 Part 11 ready

Applications

Chemiluminescence Western, Northern or Southern blot

Optional applications:

DNA and RNA gels and fluorescence stain imaging with UV-Pad or Blue-Pad
Colorimetric stained protein gels, X-Ray film, autorads, SSCP gels, colony dish and flask imaging with White-Light-Pad or UV-Pad + conversion screen
Fluorescence Western blot with Spectra Capsules

Technologies & Innovation

Apps Studio
3D Dynamics Scan
SuperResolution
High Sensitivity Reading (HSR) technology
PadBox™
ImageMaster™ assistant
Clarity™

Options

Optional Spectra Capsules innovative concept for a customized choice of up to 7 powerful filtered optic light capsules:

**365nm UV - 440nm - 480nm - 530nm
640nm - 680nm - 740nm - 780nm**

Covering a wide variety of application in the UV, Visible and the IR range.

- UV-Pad, Super-Bright-Pad, Sky-Light-Pad
Blue-Pad, White-Light-Pad
- White light or blue light conversion screen
- Advanced Bio-1D quantification software
- CFR21 Part 11 Administration Software



FUSION SOLO S

*New Edge Generation
Build Your System As You Need*

Camera & Optics

FUSION Solo 6S with the eVo-6 camera – resolution oriented camera ideal for publication

eVo-6 camera:

- Unrivalled custom made lens f/0.70
- Scientific grade CCD camera
- Grade 0, zero defect
- Image resolution: 20 megapixels
- Native resolution: 2838×2224
- -55° C maximum cooling differential from ambient
-30°C absolute and regulated cooling via three stages Peltier thermoelectric cooler
- High Sensitivity reading (HSR) technology
- USB-3 connection

Ease Of Use

One-Click-to-the-Image™
Auto-exposure
Auto-focus
Auto-lighting

Hardware

Smart Darkroom technology:

- 6 positions filter wheel
- Software control of the lighting
- Automatic recognition of the sample position
- Automatic visible lighting adjustment
- A312nm UV PAD

Steel and stainless steel darkroom for long lasting robustness. Wide access door with UV safety shut-off
Built-in slide-out tray for interchangeable Pad.

Software

Free software for image acquisition with full GLP compliance. Molecular weight calculation, band quantification, colony counting, distance calculation, text annotation and image enhancement included.

CFR21 Part 11 ready

Applications

Chemiluminescence Western, Northern or Southern blot

Optional applications:

DNA and RNA gels and fluorescence stain imaging with UV-Pad or Blue-Pad
Colorimetric stained protein gels, X-Ray film, autorads, SSCP gels, colony dish and flask imaging with White-Light-Pad or UV-Pad + conversion screen
Fluorescence Western blot with Spectra Capsules

Technologies & Innovation

Apps Studio
3D Dynamics Scan
SuperResolution
High Sensitivity Reading (HSR) technology
PadBox™
ImageMaster™ assistant
Clarity™

Options

Spectra Capsules Adapter: Upgradable Spectra Capsules innovative concept for a customized choice of up to 7 powerful filtered optic light capsules:

**365nm UV - 440nm - 480nm - 530nm
640nm - 680nm - 740nm - 780nm**

Covering a wide variety of application in the UV, Visible and the IR range.

- White light or blue light conversion screen
- Advanced Bio-1D quantification software
- CFR21 Part 11 Administration Software



FUSION SOLO X

*New Edge Generation
Build Your System As You Need*

Camera & Optics

FUSION Solo 6X with the eVo-6 camera – resolution oriented camera, ideal for publication

eVo-6 camera:

- Unrivalled custom made lens f/0.70
- Scientific grade CCD camera
- Grade 0, zero defect
- Image resolution: 20 megapixels
- Native resolution: 2838x2224
- -55° C maximum cooling differential from ambient
-30°C absolute and regulated cooling via three stages Peltier thermoelectric cooler
- High Sensitivity reading (HSR) technology
- USB-3 connection

Ease Of Use

One-Click-to-the-Image™
Auto-exposure
Auto-lighting

Hardware

Smart Darkroom technology:

- 5 sample tray positions
- Software control of the lighting
- Automatic visible lighting adjustment

Steel and stainless steel darkroom for long lasting robustness. Wide access door.

Software

Free software for image acquisition with full GLP compliance. Molecular weight calculation, band quantification, colony counting, distance calculation, text annotation and image enhancement included.

CFR21 Part 11 ready

Applications

Chemiluminescence Western, Northern or Southern blot

Technologies & Innovation

Apps Studio
3D Dynamics Scan
High Sensitivity Reading (HSR) technology
ImageMaster™ assistant

SPECTRA CAPSULE

The Spectra Light Capsules are powerful fluorescence exciters with focused light for uniform illumination and enhanced power. Equipped with primary and secondary optics, the Light Capsules are categorized as Laser Class II due to their intense power.



MULTISPECTRAL IMAGING





PULSE LIGHT




LASER CLASS II



NARROW BANDPASS FILTERS




Exciter Capsules



Chip material : AlGaInP, InGaIn or AlGaAs
Filter blocking index: O.D. 5.5
Laser Class II

Emission Filters




Focal disk for enhanced signal to noise ratio.
Sputtered magnetron technology.
Hard coated.

Our standard range of 8 Light Capsules allow you a wide variety of possible applications in the UV, the visible and the IR ranges.


CAPSULE OF LIGHT SPECTRUM

530nm




Peak wavelength : 530nm
Chip material : AlGaInP
Blocking index: O.D. 5.5
Laser Class II

480nm




Peak wavelength : 480nm
Chip material : AlGaInP
Blocking index: O.D. 5.5
Laser Class II

440nm



Peak wavelength : 440nm
Chip material : AlGaInP
Blocking index: O.D. 5.5
Laser Class II

365nm




Peak wavelength : 365nm
Chip material : InGaN
Blocking index: O.D. 5.5
Laser Class II

Spectrum and peak values may differ slightly from the typical values and spectrum above.

The Spectra Light Capsules offers proven reliability and superior performance.


CAPSULE OF LIGHT SPECTRUM

780nm




Peak wavelength : 780nm
Chip material : AlGaAs
Blocking index: O.D. 5.5
Laser Class II

740nm




Peak wavelength : 740nm
Chip material : AlGaAs
Blocking index: O.D. 5.5
Laser Class II

680nm



Peak wavelength : 680nm
Chip material : AlGaInP
Blocking index: O.D. 5.5
Laser Class II

640nm




Peak wavelength : 640nm
Chip material : AlGaInP
Blocking index: O.D. 5.5
Laser Class II

Spectrum and peak values may differ slightly from the typical values and spectrum above.

Steeper edges, precise wavelength accuracy, and carefully optimized blocking mean better contrast and faster measurements.


EMISSION FILTER SPECTRUM

650nm




Typical Range: 640-670nm
Sputtered magnetron technology.
Hard coated.

600nm




Typical Range: 580-640nm
Sputtered magnetron technology.
Hard coated.

550nm



Typical Range: 550-580nm
Sputtered magnetron technology.
Hard coated.

500nm




Typical Range: 530-550nm
Sputtered magnetron technology.
Hard coated.

Spectrum and peak values may differ slightly from the typical values and spectrum above.

Our filter combines the most sophisticated ion-beam-sputtering deposition systems, with our proprietary aperture disk for enhanced signal to noise ratio.


EMISSION FILTER SPECTRUM

850nm




Typical Range: 830-870nm
Sputtered magnetron technology.
Hard coated.

800nm




Typical Range: 800-840nm
Sputtered magnetron technology.
Hard coated.

750nm



Typical Range: 710-760nm
Sputtered magnetron technology.
Hard coated.

700nm



Typical Range: 690-720nm
Sputtered magnetron technology.
Hard coated.

Spectrum and peak values may differ slightly from the typical values and spectrum above.



HEADQUARTER

Vilber Lourmat
(VILBER BIO IMAGING SAS)

Postal Address :
ZAC de Lamirault
Collegien
F-77601 Marne-la-Vallee cedex 3
France
Phone : +33 (0) 1 60 06 07 71
info@vilber.com

For Logistics :
24 RUE LAMIRAULT 77090 COLLEGIEN



(주)코리아바이오믹스 www.koreabiomics.com
우)05211 서울시 강동구 아리수로 93길 27, 강일타워 402호
TEL : 02-477-7470 / FAX : 02-6081-6510